



DIN WELDING NIPPLE (1)



OGIVA A SILDARE CON O-RING DIN 3865 A – ISO 8434-4
 EMBOUT À SOUDER AVEC O-RING
 SCHWEISSNIPPEL MIT O-RING-ABDICHTUNG DIN 3865 A – ISO 8434-4
 – 24° KEGEL
 BOQUILLA PARA SOLDAR DIN 3865 A – ISO 8434-4 CON JUNTA TÓRICA

Code	Thread	Dimensions					Pressure		Series
		T1	S	D1	D	L1	Bar	Psi	
		mm	mm	mm	mm	mm			L/S
TLS06W		6	1.75	2.5	6	31	630	9137	L / S
TLS08W		8	2	4	8	31	630	9137	L / S
TLS10W		10	1.5	7	10	32.5	315	4568	L / S
TLS10WX2		10	2	6	10	32.5	400	5801	L / S
TLS12W		12	1.5	9	12	32.5	315	4568	L / S
TLS12WX2		12	2	8	12	32.5	400	5801	L / S
TLS12WX2.5		12	2.5	7	12	32.5	630	9137	L / S
TL15W		15	2.5	10	15	34	315	4568	L
TL18W		18	2.5	13	18	35.5	315	4568	L
TL22W		22	2.5	17	22	38.5	160	2320	L
TL28W		28	2.5	23	28	41.5	160	2320	L
TL35W		35	3	29	35	47.5	160	2320	L
TL42W		42	3	36	42	47.5	160	2320	L
TS14W		14	3	8	14	38.5	400	5801	S
TS16W		16	2	12	16	39	250	3626	S
TS16WX2.5		16	2.5	11	16	39	315	4568	S
TS16WX3		16	3	10	16	39	400	5801	S
TS20W		20	2.5	15	20	45	250	3626	S
TS20WX3		20	3	14	20	45	315	4568	S
TS20WX4		20	4	12	20	45	400	5801	S

DIN WELDING NIPPLE (2)



OGIVA A SILDARE CON O-RING DIN 3865 A – ISO 8434-4
 EMBOUT À SOUDER AVEC O-RING
 SCHWEISSNIPPEL MIT O-RING-ABDICHTUNG DIN 3865 A – ISO 8434-4
 – 24° KEGEL
 BOQUILLA PARA SOLDAR DIN 3865 A – ISO 8434-4 CON JUNTA TÓRICA

Code	Thread	Dimensions					Pressure		Series
		T1	S	D1	D	L1	Bar	Psi	
		mm	mm	mm	mm	mm	L/S		
TS25W		25	3	19	25	49.5	250	3626	S
TS25WX4		25	4	17	25	49.5	315	4568	S
TS25WX5		25	5	15	25	49.5	400	5801	S
TS30W		30	3	24	30	52	160	2320	S
TS30WX4		30	4	22	30	52	250	3626	S
TS30WX5		30	5	20	30	52	315	4568	S
TS30WX6		30	6	18	30	52	315	4568	S
TS38W		38	3	32	38	56.5	160	2320	S
TS38WX5		38	5	28	38	56.5	250	3626	S
TS38WX6		38	6	26	38	56.5	315	4568	S
TS38WX8		38	8	22	38	56.5	315	4568	S