


ADAPTOR FEMALE JIC - MALE JIC

ADATTATORE DIRITTO - FEMMINA JIC - MASCHIO JIC
 ADAPTATEUR FEMELLE E JIC - MÂLE JIC
 REDUZIERUNG IG-JIC / AG - JIC
 ADAPTADOR HEMBRA JIC - MACHO JIC

F1 - JIC
 F2 - JIC



Code	Thread		Dimensions				Pressure		
	F1	F2	H	L1	L2	L	Form	PN	Psi
Forma			mm	mm	mm	mm		Bar	
AFGJ06MJ04	9/16"	7/16"	19	19	14	33	Y	275	3988
AFGJ06MJ05	9/16"	1/2"	19	17.5	14	31.5	X	345	5003
AFGJ08MJ04	3/4"	7/16"	22	21.9	14	35.9	Y	275	3988
AFGJ08MJ05	3/4"	1/2"	22	21.9	14	35.9	Y	275	3988
AFGJ08MJ06	3/4"	9/16"	22	21.8	14.1	35.9	Y	275	3988
AFGJ10MJ04	7/8"	7/16"	27	25.2	14	39.2	Y	210	3045
AFGJ10MJ06	7/8"	9/16"	27	25.1	14.1	39.2	Y	210	3045
AFGJ10MJ08	7/8"	3/4"	27	24.3	16.7	41	X	240	3480
AFGJ12MJ04	1".1/16	7/16"	32	26.4	14	40.4	Y	210	3045
AFGJ12MJ06	1".1/16	9/16"	32	26.3	14.1	40.4	Y	210	3045
AFGJ12MJ08	1".1/16	3/4"	32	26.2	16.7	42.9	Y	210	3045
AFGJ12MJ10	1".1/16	7/8"	32	27.2	19.3	46.5	Y	240	3480
AFGJ16MJ12	1".5/16	1".1/16	41	28.9	21.9	50.8	Y	170	2465
AFGJ20MJ12	1".5/8	1".1/16	50	31.4	21.9	53.3	Y	140	2030
AFGJ20MJ16	1".5/8	1".5/16	50	31.7	23.1	54.8	Y	140	2030
AFGJ24MJ16	1".7/8	1".5/16	60	36.3	23.1	59.4	Y	105	1523

Y: Swivel nut version
 Versione con dado girevole

X: Fixed nut version
 Versione con dado fisso