


STANDARD FITTINGS

JIC 37° FEMALE- 90° ELBOW LONG DROP - THRUST WIRE NUT

FEMMINA 90° JIC SV 37° CON DADO SPINATO LONG DROP
 FEMELLE 90° JIC CÔNE 37° (ÉCROU À JONC)
 DKJ 90° BOGEN 37° JIC DICHTKOPF(UNF)+GESTIFTETE ÜBERWURFMUTTER
 HEMBRA A 90° JIC CONO 37° (TUERCA CON SEGURO) LONG DROP



| Code | Tube | | Thread | | Dimensions | | | Pressure | | |
|--------------|------|------|--------|---------|------------|----|------|----------|-----|------|
| | D.N. | Hose | Diam | T | t/1" | H | B | A | Bar | Psi |
| | Inch | mm | Inch | | mm | mm | mm | | | |
| F90J0404SPLD | -4 | 1/4" | 6.4 | 7/16" | 20 | 17 | 45 | 28.5 | 350 | 5076 |
| F90J0405SPLD | -4 | 1/4" | 6.4 | 1/2" | 20 | 17 | 45 | 28.5 | 350 | 5076 |
| F90J0406SPLD | -4 | 1/4" | 6.4 | 9/16" | 18 | 19 | 55.5 | 29.5 | 250 | 3626 |
| F90J0606SPLD | -6 | 3/8" | 9.5 | 9/16" | 18 | 19 | 55 | 35.5 | 250 | 3626 |
| F90J0608SPLD | -6 | 3/8" | 9.5 | 3/4" | 16 | 24 | 61.5 | 36.5 | 250 | 3626 |
| F90J0808SPLD | -8 | 1/2" | 12.8 | 3/4" | 16 | 24 | 61.5 | 40.5 | 250 | 3626 |
| F90J0810SPLD | -8 | 1/2" | 12.8 | 7/8" | 14 | 27 | 65 | 45 | 200 | 2901 |
| F90J1010SPLD | -10 | 5/8" | 16 | 7/8" | 14 | 27 | 65.5 | 53.5 | 200 | 2901 |
| F90J1212SPLD | -12 | 3/4" | 19 | 1.1/16" | 12 | 32 | 94.5 | 62 | 200 | 2901 |
| F90J1616SPLD | -16 | 1" | 25.4 | 1.5/16" | 12 | 38 | 132 | 77 | 160 | 2320 |